

PAC22 SERIES 2

PORTABLE AIR CONDITIONER WITH REMOTE CONDENSOR

Duty (kW/btu)

6.47 kW 22,075 btu

Air Flow (m³/h/cfm)

Max. 1359 m³/h 800 cfm

Min. 952 m³/h 560 cfm

Cooled Area Typical

156 m³ 5519 ft³

Power Supply volt/amps

230v 1ph 50hz Run 11A

Noise Level dba Av.

Indoor Max. 65 dba @ 3 mtr

Outdoor Max. 62 dba @ 4 mtr

Weight

Indoor 110 kg 222.6 lb

Outdoor 8 kg 17.6 lb

Dimensions w/l/h

Indoor 390 x 820 x 1245 mm

15 x 33.6 x 49 ins

Outdoor 565 x 285 x 520 mm

22.2 x 11.2 x 20.5 ins

Pac Line Length

5 mtr (Max. 6 = 30 mtr) 16 ft (Max. 6 = 96ft)


Control*

Automatic Thermostat

Power Consumption Av.

2400 w/h

*capable of operating down to 10°C



PAC 60

PORTABLE AIR CONDITIONER WITH REMOTE CONDENSOR

Duty (kW/btu)

16.4 kW 56,000 btu

Air Flow (m³/h/cfm)

2700 m³/h 1588 cfm

Cooled Area Typical

396 m³ 14000 ft³

Power Supply volt/amps

415v 3ph 50hz Run 12A/ph

Plug Type

BS4343 5 pin 16A

Noise Level dba Av.

Indoor 62.1 dba @ 1 mtr

Outdoor 65.1 dba @ 1 mtr

Weight

Indoor 195 kg 429.9 lb

Outdoor 140 kg 308.5 lb

Dimensions w/l/h

Indoor 950 x 511 x 2060 mm

37.4 x 20 x 81 ins

Outdoor 1010 x 690 x 670 mm

39.7 x 27 x 26.3 ins

Pac Line Length

15 mtr (Max. 2 = 30 mtr)

49 ft (Max. 2 = 98 ft)

Control

Automatic Thermostat

Power Consumption Av.

8000 w/h

