

REFRIGERANT DEHUMIDIFIER - FD30 DV



Extraction rate (max)	55 litres/24hr
Nominal extraction duty at 75% RH @ 20°C	34 litres/24hr
Air flow (max)	380 m ³ /h
Keep dry area (typical)	748 m ³
Dry out area (typical)	374 m ³
Power supply	230/110 V 1 ph 50 Hz Run 4.1/8.2 A
Plug type	BS1363 230 V BS4343 16 A 110 V
Noise level (max)	57 dBA @ 3 metres
Weight	37 kg
Dimensions (L x W x H)	363 x 363 x 805 mm
Control	Manual (humidistat option)
Average power consumption	492 W/h

DE 25 - ELECTRIC HEATER



Nominal heating duty	2.8 kW
Air flow (max)	250 m ³ /h
Typical heated area	67.6 m ³
Power supply	230 / 110 V 1 ph 50 Hz versions available Run 12.2 / 25.4 A
Plug type	BS1363 230 V or BS4343 32 A 110V
Noise level (max)	50.6 dBA @ 1 metre
Weight	11 kg
Dimensions (L x W x H)	320 x 260 x 360 mm
Control	DE25 Manual or DE25T (integral thermostat)
Average power consumption	2.8 kW/h

COOLING FAN - ASF21



Air flow (max)

3,600 m³/h

Power supply

230 or 110 V versions available 1 ph 50 Hz
Run 1.15/3 A

Plug type

BS1363 230 V BS4343 16 A 110 V

Noise level (max)

67.5 dBA @ 1 metre

Weight

10 kg

Dimensions (L x W x H)

640 x 300 x 640 mm

Control

Manual variable speed

Average power consumption

265 W/h