

REFRIGERANT DEHUMIDIFIER - HD500 DV



Extraction rate (max)	70 litres/24hr
Nominal extraction duty at 75% RH @ 20°C	34 litres/24hr
Air flow (max)	480 m ³ /h
Keep dry area (typical)	748 m ³
Dry out area (typical)	374 m ³
Power supply	230/110 V 1 ph 50 Hz Run 4.1/8.2 A
Plug type	BS1363 230 V BS4343 16 A 110 V
Noise level (max)	57 dBA @ 3 metres
Weight	59 kg
Dimensions (L x W x H)	940 x 630 x 1,110 mm
Control	Manual (humidistat option)
Average power consumption	650 W/h

DE 25 - ELECTRIC HEATER



Nominal heating duty	2.8 kW
Air flow (max)	250 m ³ /h
Typical heated area	67.6 m ³
Power supply	230 / 110 V 1 ph 50 Hz versions available Run 12.2 / 25.4 A
Plug type	BS1363 230 V or BS4343 32 A 110V
Noise level (max)	50.6 dBA @ 1 metre
Weight	11 kg
Dimensions (L x W x H)	320 x 260 x 360 mm
Control	DE25 Manual or DE25T (integral thermostat)
Average power consumption	2.8 kW/h

ASF50 - COOLING FAN



Air flow (max)	7,600 m ³ /h
Power supply	230 or 110 V versions available 1 ph 50 Hz Run 3.7/6.1 A
Plug type	BS1363 230 V BS4343 16 A 110 V
Noise level (max)	80 dBA @ 1 metre
Weight	21 kg
Dimensions (L x W x H)	840 x 345 x 820 mm
Control	Manual variable speed
Average power consumption	851 W/h